

Ecco SOLAS

Fire Extinguishers



SOLAS Approved fire extinguishers are needed for many vessels. In accordance with AS 1851 fire extinguishers must be inspected every six months. The types of Marine fire extinguishers approved include dry chemical, foam, carbon dioxide. The equipment on your vessel and your boat's construction are factors in determining which extinguisher would be most effective. Be sure to discuss your fire extinguisher options with a trained professional to choose the best fire safety devices for your application.


Dry Chemical Powder Fire Extinguishers are suitable for fighting class A,B and E fires. ABE powder extinguishers have a very good fire fighting capacity.

AFFF Foam Class A:B extinguisher. Apply to Class B liquid spills to prevent ignition.

Wet Chemical Fire Extinguishers are the best kitchen appliance hand portable fire extinguishers. They have been tested and approved for Class F specifically for kitchen hazards.

Carbon Dioxide is discharged as a white cloud of "snow" which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive.

All units Feature :
Rugged Construction
UV Rated Powder Coat Paint Finish
Pull Ring Retainer fitted on all units
Hose retainer fitted on all units with hose.




Ecco SOLAS

Fire Extinguishers

Ecco Portable
Fire Equipment



CE



Specifications		STORED PRESSURE			
AGENT	ABC				
Capacity	2 Kg	6 Kg	9 Kg	25 Kg	50 Kg
Part Number	M-FT01-02A	M-FT01-06A	M-FT01-09A	M-FT03-042B	M-FT03-047C
EN Rating	13A:55B:C	34A:183B:C	43A:183B:C	55A:IB:C	55A:IIB:C
Applicator	Nozzle	Hose & Horn			
Standard Bkt	Wall	Wall	Wall	—	—
Dims. Unit(mm)	125 x 125 x 335	170 x 170 x 535	195 x 195 x 560	450 x 450 x 1100	500 x 500 x 1200
Mass Full	3.5 kg	9.45 kg	13.2 kg	52 kg	82 kg
Cylinder Diam.	110 mm	160 mm	185 mm	250 mm	300 mm
Cylinder Height	306 mm	430 mm	455 mm	660 mm	920 mm

Ecco SOLAS

Fire Extinguishers

Ecco Portable
Fire Equipment



Specifications	STORED PRESSURE				
AGENT	AFFF		Wet Chemical	CO2	
Capacity	9 Lit	50 Lit	6 Lit	5 Kg	10 Kg
Part Number	M-FT01-09A/CE1	M-FT03-47D	M-FT01-06A-R4	M-FT02-03D	M-FT03-051C
EN Rating	21A:233B	55A:IIB:C	13A:75F	89B:C	113B:C
Applicator	Hose & Horn				
Standard Bkt	Wall	—	Wall	Wall	—
Dims. Unit(mm)	195 x 195 x 620	500 x 500 x 1200	170 x 170 x 535	170 x 140 x 770	360 x 330 x 1200
Mass Full	14 kg	85 kg	9.5 kg	13.5 kg	45 kg
Cylinder Diam.	185 mm	320 mm	160 mm	136 mm	915 mm
Cylinder Height	475 mm	920 mm	435 mm	650 mm	165 mm



CE

Specifications	CARTRIDGE OPERATED		
AGENT	ABC		AFFF
Capacity	25 Kg	50 Kg	50 Lit
Part Number	M-FT03-042D	M-FT03-047F	M-FT03-047G
EN Rating	55A:IB:C	55A:IIB:C	55A:IIB:C
Applicator	Hose & Horn		
Dims. Unit(mm)	450 x 450 x 1100	500 x 500 x 1200	500 x 500 x 1200
Mass Full	56 kg	90 kg	93 kg
Cylinder Diam.	250 mm	300 mm	320 mm
Cylinder Height	660 mm	920 mm	920 mm
Cartridge	1kg CO2	1.6kg CO2	0.7kg CO2

